

# QuickTask MHQT Mop Head

## Single use two-ply 100% polyester flat mop head

QuickTask MHQT Flat Mop Heads are manufactured from 100% 2-ply polyester around a polyester / rayon core so are ideal for even the highest grade of cleanroom as they generate very small numbers of particle and fibres.

These mop heads have been specifically designed for use with Contec's Mop Saturation Systems. With high absorbency the mops are suitable for single use saturation, giving a surface coverage up to approximately 20 sqm.

The mop heads are designed for hands-free fitting to the mop head frame when used with an "A frame" applicator. The heads are compatible with the QuickTask Magnetic Mop Head Frames 2906 and 2699, and the QuickTask Polypropylene Mop Frame 2740.

QuickTask MHQT Flat Mop Heads are suitable for the application of disinfectants and removal of light soil, residues and biofilms. Designed for single use, the mop heads are compatible with a wide range of chemicals and disinfectants.

MHQT0150 is gamma irradiated at no less than 25kGy, with certificates of conformity and irradiation available for every batch. Five mops are double bagged for easy transfer into the cleanroom environment.



Features	Benefits
100% 2-ply polyester mop heads	<ul> <li>Low levels of particle and fibres</li> <li>Compatible with a wide range of disinfectants and detergents</li> <li>Excellent surface contact</li> </ul>
High sorbency	<ul> <li>Approx 20 sqm coverage per mop so ideal for presaturation systems</li> <li>Saves time as reduces number of visits back to a bucket system</li> </ul>
Available sterile	Suitable for use in Grade B cleanrooms
Suitable for hands free mop application *	<ul><li>Easy and convenient to use</li><li>Reduces cross contamination</li></ul>
Double bagged	Facilitates transfer into cleanrooms and critical environments

\* with appropriate hardware

Part No.	Description	Size	Packaging
MHQT0100	QuickTask Quiltec MHQT Mop Head	39 x 13 cm	5 mops per bag 8 bags per case
MHQT0150	QuickTask Sterile Quiltec MHQT Mop Head	39 x 13 cm	5 mops per bag 8 bags per case

Copyright © 2023 Contec, Inc. All rights reserved. INT153 120423

Contact us: infoeu@contecinc.com contecinc.com/eu Vannes France tel: +33(0) 2 97 43 76 98 Spartanburg, SC United States tel: +1 (864) 503-8333



Product Information		
Material	• Two-ply 100% knitted polyester/synthetic fibrefill core	
Construction	Multi-layer sewn lamination	
Environment	• ISO 5-8 Grade B for sterile; C/D for nonsterile	
Shelf life	• Sterile 2 years from manufacturing date	



Technical Data					
Attribute (units)	Typical Value	Test Method			
Mop weight, dry; (g/mop)	57	CTM004-03			
Sorbent capacity; (mL/mop)	345	CTM004-03			
Non-volatile residue, NVR		IEST-RP-CC004.3, Sec. 7.1.2			
In deionized water; (g/m²)	0.005				
In isopropyl alcohol; (g/m²)	0.010				
Particles, readily releasable		IEST-RP-CC004.2, Sec. 5.2			
Particles <u>&gt;</u> 0.5µm; (x10 <sup>6</sup> /mop)	33.88				
Fibres ≥ 100µm; (x 10³/mop)	3.60				

#### Notes

a) The data shown are typical values and should not be used

b) Valid product specifications.
b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.

c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Test Methods

CTM Contec Test Method

IEST-RP-CC004.3 Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments, Institute of Environmental Sciences and Technology, Rolling Meadows IL

# **Recycling Key**



### **Packaging Information**

Packaging Materials Outer bags Case	Low density polyethylene (LDPE) Corrugated fibreboard (PAP)			6) 6)	
Packaging Configuration MHQT0100 MHQT0150	EA/OB1 5 5	OB1/CS 8 8	EA/CS 40 40		

EA = Each, PCH = Pouch, OB = Outer Bag 1/2/3, CS = Case

For more information or to request a sample, email infoeu@contecinc.com or phone +33 (0) 2 97 43 76 98.

Contact us: infoeu@contecinc.com contecinc.com/eu

Vannes France tel: +33(0) 2 97 43 76 98 Spartanburg, SC **United States** tel: +1 (864) 503-8333

